

1

2

3

4

5

6

7

8

9

10

11

符合“DLK环境管理物质技术标准”

符合USB3.0协会规范标准”

工程变更通知单
ECN(DCN) NO.

版本
REV

日期
DATE

说明
DESCRIPTION

变更
CHANGE

核准
APPRO.

U3A82 D-09 L M5 R N1 0

① ② ③ ④ ⑤ ⑥ ⑦

① PRODUCTION CODE (产品编码):
U3A82: USB 3.0 A/F R/A 9.4H STD.

② CHARACTER (特征):
D:DIP TYPE

③ POSITION (位数):
09: 9PIN

④ COLOR OF HOUSING(本体颜色):
L:BLUE (300C)

⑤ PLATING OF CONTACT(端子电镀):
M5 : Au 30U” AND MATTE TIN 100U” PLATED

⑥ PACKAGE(包装):
R :REEL PACKAGE

⑦ PLATING OF SHELL(铁壳电镀):
N1 :Ni plated

③

DLK LOGO

②

16.50±0.30

14.60±0.30

9.40±0.25

6.50±0.30

0.20±0.05

3.50±0.10

2.40±0.15

11.78±0.25

7.22±0.25

8.00±0.15

2.00±0.15

2.00±0.15

0.40±0.10

7.00±0.15

1.50±0.15

11.10 min.

12.50±0.25

8.00±0.20

7.00±0.20

2.00±0.20

5.12±0.25

10.10±0.25

12.80±0.30

2.60±0.15

1.84±0.20

2.80±0.15

8.00

2.00

1.50

3.50

1.00

2.00

7.00

12.80

11.78

2.20

0.70

A 区

B 区

C 区

端子镀金测点

1.10

5.70

4.80

PCB LAYOUT(T1.2~1.6)TOP VIEW

CONTACT PLATING DIAGRAM

电镀规格:

C2680/0.2T

Ni 99.99%(Thickness 50u”min)

Au (Thickness 30u”min)

CONTACT AREA

C2680/0.2T

Ni 99.99%(Thickness 50u”min)

Sn 99.99%(Thickness 100u”min)

CONTACT FOOT

SUS430/0.3T

Ni 99.99%(Thickness 50u”min)

SHELL

德力康电子科技有限公司

DLK DELIKANG ELECTRONICS TECHNOLOGY CO.,LTD

GENERAL TOLERANCE
UNLESS OTHERWISE NOTED

Angle ±2°

X. ±0.38

.X ±0.30

.XX ±0.25

.XXX ±0.15

A4

C 名称
TITLE:

档案名称
FILE NAME.

DRAWING

UNIT:

mm

SCALE

1:1

SHEET: 1 of 1

料号
PART NO.

档案号
PART NO:
(OLD)

CHECKED

APPROVED

cw.yan

USB 3.0 A/F R/A 9.4H STD.

C-U3A82-00-00

yh.wang

mm

1:1

U3A82D-09LM5RN10

4

COVER

1

LCP

UL94V-0

3

CONTACT

9

C2680

Au PLATED

2

SHELL

1

SUS430

Ni PLATED

1

HOUSING

1

LCP

UL94V-0

NO.

ITEM

Q'TY

DESCRIPTION

FINISH