

1

2

3

4

5

6

7

8

9

10

11

符合“DLK环境管理物质技术标准”

符合USB3.0协会规范标准”

工程变更通知单
ECN(DCN) NO.

版本
REV

日期
DATE

说明
DESCRIPTION

变更
CHANGE

核准
APPRO.

U3A20 D-09 * M5 Y N2 0

① ② ③ ④ ⑤ ⑥ ⑦

① PRODUCTION CODE (产品编码):
U3A20: USB 3.0 A/F R/A 6.96H STD.

② CHARACTER (特征):
D:DIP TYPE

③ POSITION (位数):
09: 9PIN

④ COLOR OF HOUSING(本体颜色):
B:BLACK
Y:YELLOW

⑤ PLATING OF CONTACT(端子电镀):
M5 : Au 30U” AND TIN 50U” PLATED

⑥ PACKAGE (包装):
Y :TRAY PACKAGE

⑦ PLATING OF SHELL(铁壳电镀):
N2 :Ni plated

12.50±0.10

11.10±0.1

1.00±0.05

3.50±0.05

1.84±0.05

5.12±0.10

0.45

2.00±0.1

7.00±0.2

8.00±0.2

12.8

9

8

7

6

5

4

3

2

1

16.5

6.0

13.8

2.60

11.0Min

2.4±0.15

2.0

3.5±0.15

11.78

6.96±0.25

DLK LOGO

8.00

4.0

1.50

3.5

9-ø0.70±0.05

2-2.2

7.00

12.8

2-1.0

2.0

PCB LAYOUT(T1.0~1.6)TOP VIEW

A区

C区

B区

端子镀金测点

1.10

4.80

5.70

CONTACT PLATING DIAGRAM

A区:打镍底12u”
B区:先镀镍12u”再单面刷金,
测点规格见料号.
C区:先镀镍12u”再镀锡50u”

电镀规格:

C5191/C2680 0.2T

Ni 99.99%(Thickness 12u”min)

Au(见料号说明)

CONTACT AREA

C5191/C2680 0.2T

Ni 99.99%(Thickness 12u”min)

Sn 99.99%(Thickness 50u”min)

CONTACT FOOT

SUS430 0.3T

Ni 99.99%(Thickness 40u”min)

SHELL

名称
TITLE:

档案名称
FILE NAME.

DRAWING

UNIT:

德力康电子科技有限公司
DLK DELIKANG ELECTRONICS TECHNOLOGY CO.,LTD

USB 3.0 A/F R/A 6.96H STD.

C-U3A20-00-02

mm

料号
PART NO.

U3A20D-09*M5YN20

CHECKED

王永辉

APPROVED

严成旺

SCALE

1:1

SHEET: 1 of 1

NO.

ITEM

Q'TY

DESCRIPTION

FINISH

4

COVER

1

PA9T

UL94V-0

3

CONTACT

9

C5191/C2680

Au PLATED

2

SHELL

1

SUS430

Ni PLATED

1

HOUSING

1

PA9T

UL94V-0

1

2

3

4

5

6

7

8

9

10

11