

1	2	3	4	5	6	7	8	9	10	11		
符合“DLK环境管理物质技术标准”							工程变更通知单 ECN(DCN) NO.	版本 REV	日期 DATE	说明 DESCRIPTION	变更 CHANGE	核准 APPRO.
符合USB3.0协会规范标准”							KSECN18059	A	20181016	NEW RELEASE	—	—
SPECIFICATION												
Materials:												
Insulator: Thermoplastic,Glass Filled,UL94V-0												
Contact: Cu Alloy, 0.25mm												
Plastic: LCP HF Blue or Black												
Shell: SUS430-H,0.3mm												
lectrical:												
Insulation Resistance:1000 MO min.												
Contact Resistance: 30 mΩ max.initial												
Dielectric Withstanding Voltage: 500V AC for 1 minute												
Current Rating: 1.5 A max.per contact at 30℃ T-Rise												
Voltage: 30V AC(rms)												
Operating Temperature Range: -55 ℃ to +85℃												
Finish												
Shell: 50u” Ni												
Contact: mating area: Gold flash over min.50u” Ni												
Solder tail:100u” tin over min.50u” Ni												
U3A20 D-09 L M4 Y N2 P HF												
① ② ③ ④ ⑤ ⑥ ⑦												
① PRODUCTION CODE (产品编码):												
U3A20: USB 3.0 A/F R/A 6.96H STD.												
② CHARACTER (特征):												
D:DIP TYPE												
③ POSITION (位数):												
09: 9PIN												
④ COLOR OF HOUSING(本体颜色):												
L:BLUE (300C)												
⑤ PLATING OF CONTACT(端子电镀):												
M4 : Au 15U” AND MATTE TIN 100U” PLATED												
⑥ PACKAGE(包装):												
Y :TRAY PACKAGE												
⑦ PLATING OF SHELL(铁壳电镀):												
N2 :Ni plated												
产品净重: 2.09g							德力康电子科技有限公司 DLK DELIKANG ELECTRONICS TECHNOLOGY CO.,LTD					
4 COVER 1 LCP UL94V-0							C 名称 TITLE: USB 3.0 A/F R/A 6.96H STD.					
3 CONTACT 9 C5191 Au PLATED							档案名称 FILE NAME. C-U3A20-00-0P 料号 PART NO: U3A20D-09LM4YN2PHF					
2 SHELL 1 SUS430 Ni PLATED							DRAWING 王永辉 CHECKED APPROVED					
1 HOUSING 1 LCP UL94V-0							UNIT: mm SCALE 1:1 SHEET: 1 of 1					
NO. ITEM Q'TY DESCRIPTION FINISH							A4 6.96H STD.					
1	2	3	4	5	6	7	8	9	10	11		